

« Light » Adaptor

For refrigerant fluids



High precision, lightness and versatility

- Compatible with a wide range of refrigerant fluids
- Easier maintenance
- Enhanced ergonomics
- Adaptable to most of your filling machines

Designed to optimize the day-to-day operations of production and maintenance teams, our Light adaptor fits a wide range of refrigerant filling equipment

5 reasons to choose the Light adaptor

MAINTENANCE

- Easy access to valves and filters
- Optimised Fives valve life (120 000 cycles)
- Seals change every 60 000 cycles



ERGONOMICS

- Reduction of musculoskeletal disorders ($\varnothing < 40\text{mm}$)
- 15% weight reduction ($< 1,2\text{kg}$)
- Reduced size to fit all types of engine



INTEGRATION

- Turnkey solution that can be integrated with all Filling | Sealing equipment
- High filling pressure (18 bar) for a wide range of gases



PRECISION

- Improved accuracy and filling rate
 - $\pm 10\text{g}$ at 160g/s (HFO)
 - $\pm 1\text{g}$ at 14g/s (R290)



SAFETY

- Increased operator safety (no ATEX zone required)
- Complies with ATEX Directive 2014/34/UE



The information contained in this document is for information purposes only and does not constitute a legal obligation or warranty of any kind, expressed or implied.

CONTACT US

contact-fillingsealing@fivesgroup.com

T +33 (0)2 40 32 06 06

Fives Filling & Sealing

Parc d'Activités de la Forêt – 17 rue de la Communauté – Le Bignon, 44140 – France

www.fivesgroup.com



fives

Industry can do it